



Firma: ISCom d.o.o.
Adresa: T.C. "Danubius" Karađorđeva 12,
lokali 28, 156 i 156a
Telefon: 026/4-100-500, 069/4-100-500
Fax:
PIB: 104927929
E-mail: prodaja@iscom.rs

Tenda MW3 AC1200 dual band distribution mesh WiFi system 200m2 2PACKS

Šifra: 10449
Kategorija proizvoda: Wireless AP i Ruteri
Proizvođač: TENDA

Cena: 6.811,00 rsd.



MW3 is a 1200Mbps dual band distribution mesh WiFi system designed for 100-300? houses, bringing you with whole home WiFi coverage, as well as fast and stable internet connection. Pack of 3 provides you with up to 300? WiFi range; while pack of 2 provides you with up to 200? WiFi range. Compliant with IEEE 802.11v and IEEE 802.11r seamless roaming protocols, MW3 supports automatic network optimization and automatic routing selection, allowing you to enjoy more stable and flexible wireless network.

Standard&Protocol: IEEE802.3, IEEE802.3u
Interface: 2 Ethernet ports per mesh node
WAN and LAN on primary mesh node
Both act as LAN ports on additional mesh nodes
Antenna: 2*3dBi internal dual band antennas
Button: 1 reset button
Power: Input:100-240V—50/60Hz
Dimension: 90 x 90 x 90mm
Wireless Standards: IEEE 802.11ac/a/n 5GHz
IEEE 802.11b/g/n 2.4GHz
Wireless Frequency2.4G: 2400MHz-2483MHz
5G: 5150MHz-5250MHz or 5725MHz-5825MHz
Data Rate: 5GHz: Up to 867Mbps
2.4GHz: Up to 300Mbps
Frequency: Simultaneous dual band 2.4GHz & 5GHz
Basic Features:SSID Broadcast
Beamforming
Wireless Security: Mixed WPA/WPA2-PSK(default)
Wireless roaming: Comply with IEEE802.11v/r
Internet Connection Type: PPPoE, Dynamic IP, Static IP, Bridge Mode
DHCP ServerDHCP Server
DHCP Client List
Virtual Server: Port Forwarding
UPnP
QoS: Support Smart QoS
Firewall: Forbid UDP flood attack
Forbid TCP flood attack
Forbid ICMP flood attack
DNS: Support manually setting DNS server
VPN: IPsec pass through
PPTP pass through
L2TP pass through
Other: Parental Control
Guest Network
Firmware upgrade online

Reset to factory settings

Setup Requirements: A mobile device running Android 4.0+ or iOS 8+

Temperature: Operating Temperature: 0? ~ 40?

Storage Temperature: -40? ~ 70?.

Humidity: Operating Humidity:10% ~ 90% RH non-condensing

Storage Humidity: 5% ~ 90%RH non-condensing.

Certification: FCC, CE, RoHS, EAC, IC

Package Content: (2-pack) 2 identical mesh nodes

2 power adapters

Quick install guide

1 ethernet cable