



Firma: ISCom d.o.o.
Adresa: T.C. "Danubius" lokali 28, 156 i 156a,
Karađorđeva 12
Telefon: 026/4-100-500, 026/464-11-64
Fax:
PIB: 104927929
E-mail: prodaja@iscom.rs

Tenda O6 outdoor long range 5GHz 433Mbps

Šifra: 20009

Kategorija proizvoda: Wireless AP i Ruteri

Proizvođač: TENDA

Cena: **12.622,00** rsd.



Dimension 270*94.86*67.5mm Frequency Range 5GHz Maximum wireless speed 433Mbps CPU Processor Broadcom 800MHz GND Terminal 1 Interface 1*GE PoE/WAN/LAN port Mode Switch Station: The device only work in Station mode Off: The device work on AP/Station/Universal Repeater/WISP/Router mode AP: The device only work in AP mode Button Reset: Press 10 seconds or more to restore to default settings Bridge: Press 3 seconds and release it to bridge uplink AP Antenna 16dbi Directional Antenna Antenna Beamwidth Horizontal: 30° Vertical: 15° Maximum Consumption 9W Lightning Protection 6KV Waterproof Level IP64 LED LAN, LED1, LED2, LED3 Power Supply 24v 0.5A PoE Injector Operating mode AP/Station/Universal Repeater/WISP/Router Standard Protocol IEEE 802.11ac/n/a Wireless Speed Enable/Disable Wireless Radio SSID Hidden Wireless Client isolation Sensitivity Threshold WMM Capable APSD Capable Wireless Access Control Wireless Client list Wireless Security 64/128 WEP, WPA-PSK, WPA2-PSK, WPA WPA2-PSK, WPA, WPA2 Transmit Power Adjustable power by 1dBm Reception Sensitivity MCS0: -90dbm MCS7: -72dbm DHCP Server DHCP Server Clients list VPN Pass-through PPTP, L2TP Ping Watchdog Support Speed Test Support Remote Web access Support Schedule Reboot Support Page Timeout Support DynDNS noip, dyndns.org Network Diagnoses Ping, Traceroute, Signal Scan Management Tool Time Date Setting System Log Firmware update Backup/Restore Configuration Username Management Temperature Operating Temperature: -20° ~ 55° Storage Temperature: -40° ~ 70° Humidity Operating Humidity: 10%~90% non-condensing Storage Humidity: 10%~90% non-condensing Default Settings IP Address: 192.168.2.1 Login Username: admin Login Password: admin Certification FCC/CE/RoHS