



Firma: ISCom d.o.o.
Adresa: T.C. "Danubius" Karađorđeva 12,
lokali 28, 156 i 156a
Telefon: 026/4-100-500, 069/4-100-500
Fax:
PIB: 104927929
E-mail: prodaja@iscom.rs

Tenda AC6 AC1200 Smart Dual-Band 10/100 WIFI Router, 2.4+5GHz, 1W/4L, 2x5dBi

Šifra: 20045

Kategorija proizvoda: Wireless AP i Ruteri

Proizvođač: TENDA

Cena: 2.999,00 rsd.



AC6 is a
Smart
Dual-
band
WiFi
Router
with
strong
signal
and
stable

performance. It supports 5th generation Wi-Fi standard 802.11ac and the concurrent dual-band speed is up to 1167Mbps. 900MHz CPU from Broadcom offers fast stable performance. AC6 has 2x through-wall ability than normal routers with its independent power amplifiers, beamforming+ Intelligent technology and 4x 5dBi HG antennas. You can enjoy lag-free gaming and uninterrupted video streaming anytime anywhere. Additionally, AC6 supports smart power saving technology, App remote management, creates a low-power consumption and smart eco-friendly life for your whole family. Standard Protocol: IEEE802.3, IEEE802.3u Interface: 1*10/100Mbps WAN port 3*10/100Mbps LAN ports Antenna: 4*5dBi external antennas Button: 1*WiFi on/off, 1* Reset/WPS button Power: Input:100-240V—50/60Hz, 0.2A Output:DC 12V==1A Dimension: 220*141.5*49mm LED: System*1, WAN*1, LAN*1, 2.4G*1, 5G*1, WPS*1 Wireless Standards: IEEE 802.11ac/a/n 5GHz IEEE 802.11b/g/n 2.4GHz Data rate 5GHz: Up to 867Mbps 2.4GHz: Up to 300Mbps Frequency: Simultaneous dual band 2.4 5GHz Transmit Power CE: 20dBm(2.4G) 23dBm(5G) FCC: 30dBm Basic Features: SSID Broadcast: Enable/Disable Transmission Power: high, medium, low Beamforming Wireless Security WPA-PSK/WPA2-PSK, WPA/WPA2 Wireless Security: Enable/Disable WPS(WiFi Protected Set-up) fast encryption Internet Connection Type: PPPoE, Dynamic IP, Static IP PPPoE(Russia), PPTP(Russia), L2TP(Russia) Operating Mode: -Wireless Router Mode -Universal Repeater Mode -WISP Mode DHCP Server: DHCP Server DHCP Client List DHCP Reservation Virtual Server: Port Forwarding DMZ Host UPnP Security: Client Filter Parental Control(support black list and white list) Remote Web Management Firewall: Forbid UDP flood attack Forbid TCP flood attack Forbid flood attack Forbid WAN PING from internet DDNS: Support DynDNS, No-ip, 3322.org, Oray.com, 88ip VPNIPsec pass through PPTP pass through L2TP pass through PPTP server PPTP client L2TP client Features Smart WiFi Schedule Smart Power Saving Smart LED on/off Tenda Cloud Tenda App Other Bandwidth Control Guest Network IPTV MAC Clone Static Routing System Log Backup Restore configurations Firmware upgrade online Firmware upgradeable via browser Temperature Operating Temperature: 0? ~ 40? Storage Temperature: -40? ~ 70?. Humidity Operating Humidity: 10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90% RH non-condensing. Default Settings Default Access: tendawifi.com Package Content AC1200 Smart Dual-Band WiFi Router Power Adapter Install Guide Ethernet Cable

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.