



Firma: ISCom d.o.o.  
Adresa: T.C. "Danubius" Karađorđeva 12,  
lokali 28, 156 i 156a  
Telefon: 026/4-100-500, 069/4-100-500  
Fax:  
PIB: 104927929  
E-mail: prodaja@iscom.rs

Tenda AC11 AC1200 wireless dual band ruter  
2.4+5GHz, 1W/3L, Gbit, 1Ghz cpu 128mb,  
5x6dBi 12V/1A

Šifra: 33080

Kategorija proizvoda: Wireless AP i Ruteri

Proizvođač: TENDA

**Cena: 5.790,00 rsd.**



AC11 is  
a high-

performance WiFi router designed with full Gigabit WAN and LAN ports, removing the bottleneck of wired ports speed when working with faster bandwidth of optical fiber.

**Strong Dual Band WiFi Signal for Multi-wall Penetration**

With the new generation 802.11ac wave 2.0 standard, AC11 offers a concurrent dual band data rate of as high as 1167 Mbps. Wireless signal boosting technology both on 2.4 GHz and 5 GHz bands broadens your WiFi coverage, and Beamforming+ technology makes WiFi signal of AC11 outstanding behind multiple walls.

**Innovative MU-MIMO technology**

With innovative MU-MIMO, the breakthrough of the new generation 802.11 ac standard, AC11 can communicate with multiple devices at a time, shortening latency and improving quantities of connected devices.

**5\*6dBi External Antennas for Better WiFi Signal**

Designed with 5\*6dBi external dual band antennas, combined with Beamforming signal tracing technology, the Wi-Fi signal is aggregated into a beam directly towards users' device to ensure the best experience.

**Configuration-free for quick setup**

What if you forget your PPPoE user name or password, or you cannot login to the web UI of the router for setup? AC11 can eliminate your concern by migrating your PPPoE user name and password from your original router.

**Function-rich WiFi router**

- ? Supports Parental Control
- ? Supports Client Filter
- ? WiFi Repeater to expand WiFi coverage
- ? Guest network for higher network security
- ? Supports IPv6, provider higher access speed
- ? WiFi Schedule for smart life and green environment

AC11

**Hardware**

**Standard&Protocol**

IEEE802.3, IEEE802.3u, IEEE802.3ab

**Interfaces**

1\*10/100/1000Mbps WAN port

3\*10/100/1000Mbps LAN ports

**Antenna**

5\*6dBi external antennas

**Button**

1\* WPS/Reset button, 1\*WiFi ON/OFF

**Power**

Input:AC 100-240V~50/60Hz, 0.4A  
Output:DC 12V 1A  
Dimension  
8.66 \* 5.57 \* 1.93 in (220\*141.5\*49mm)  
LED Indicator  
Sys\*1,WAN\*1, LAN\*1,WiFi/WPS\*1  
Wireless  
Wireless Standard  
IEEE 802.11ac wave2/a/n 5GHz  
IEEE 802.11b/g/n 2.4GHz  
Data Rate  
5GHz: Up to 867Mbps  
2.4GHz: Up to 300Mbps  
Frequency  
Simultaneous dual band 2.4 & 5GHz  
Transmission Power  
CE:  
<20dBm(2.4G)  
<23dBm(5G)  
FCC:<30dBm  
Basic Features  
SSID Broadcast: Enable/Disable  
Transmission Power: high, medium, low  
Beamforming  
MU-MIMO  
Wireless Security  
WPA-PSK/WPA2-PSK, WPA/WPA2  
Wireless Security : Enable /Disable  
Software  
Internet Connection Type  
PPPoE, Dynamic IP, Static IP  
Support automatic access detection  
Supports broadband account automatic transfer  
Operating Mode  
Wireless Router Mode  
Universal Repeater Mode  
WISP Mode  
AP Mode  
DHCP Server  
DHCP Server  
DHCP Client List  
DHCP Reservation  
Virtual Server  
Port Forwarding  
DMZ Host  
UPnP  
Security  
Client Filter(supports black list and white list)  
Parental Control(supports black list and white list)  
Remote Web Management  
Firewall  
Forbid UDP flood attack  
Forbid TCP flood attack  
Forbid flood attack  
Forbid WAN PING from internet  
DDNS  
Support DynDNS, 88ip  
VPN  
IPsec pass through  
PPTP pass through  
L2TP pass through  
Special Features  
PPPoE Username/password Clone  
Smart WiFi Schedule  
Smart Power Saving  
Smart LED on/off  
Tenda Cloud  
Tenda App  
Others  
Broadband management

MAC address clone  
System Log  
Backup & Restore configurations  
Firmware upgrade from local  
Others  
Temperature  
Operating Temperature: 0? ~ 40?  
Storage Temperature: -40? ~ 70?  
Humidity  
Operating Humidity:10% ~ 90% RH non-condensing  
Storage Humidity: 5% ~ 90%RH non-condensing.  
Default Settings  
Default Access: tendawifi.com or http://192.168.0.1  
Certification  
CE/FCC/RoHS  
EIRP Power (Max)  
2.400-2.4835GHz: 19.95dBm (EIRP)  
5.150-5.250GHz: 22.90dBm (EIRP)  
Package Contents

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.