



Firma: ISCom d.o.o.
Adresa: T.C. "Danubius" Karađordeva 12,
lokali 28, 156 i 156a
Telefon: 026/4-100-500, 069/4-100-500
Fax:
PIB: 104927929
E-mail: prodaja@iscom.rs

ASUS ROG STRIX B760-A GAMING WIFI matična ploča(PLO03462)

Šifra: 42790

Kategorija proizvoda: Intel matične ploče
Proizvođač: ASUS

Cena: **29.661,00** rsd.



Audio	Broj kanala: Model: Napomena:	8 (7.1) ROG SupremeFX Audio Cover, Jack-detection, Multi-streaming, Premium audio capacitors, Dedicated audio PCB layers, SupremeFX Shielding, Savitech SV3H712 AMP
Fizičke karakteristike	Format: Dimenzije: Fiksirajući otvori:	ATX 305mm x 244mm 9
Memorija	Tip memorije: Memorijski slotovi: Podržane memorije:	DDR5 4 6.000MT s (O.C.), 5.800MT s (O.C.), 7.200MT s (O.C.), 7.000MT s (O.C.), 6.800MT s (O.C.), 6.600MT s (O.C.), 6.400MT s (O.C.), 6.200MT s (O.C.), 5.600MT s, 5.400MT s, 5.200MT s, 5.000MT s, 4.800MT s, 7.600MT s (O.C.), 7.400MT s (O.C.), 7.800MT s (O.C.)
Mreža	Žična mreža (LAN): Wi-Fi: Wi-Fi standard:	2.5GBase-T (Gigabit) Da Wi-Fi 6E (802.11ax)
Osnovne karakteristike	Procesorsko ležište (socket): Čipset: Grafika:	Intel 1700 Intel B760 Upotreba grafike iz procesora
Ostale karakteristike	Podržane tehnologije:	AI Noise Cancelation, ASUS CrashFree BIOS 3, ASUS EZ Flash 3, ASUS UEFI BIOS EZ Mode, SafeSlot, Q-DIMM, Q-Slot, SafeDIMM, ProCool, PCIe Slot Q-Release, M.2 Q-Latch, Sonic Radar III, Sonic Studio III, ROG CPU-Z, Sonic Suite Companion, VRM heatsink design, Extreme Engine Digi+, Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green]), Aura RGB header, DTS Sound Unbound, GameFirst VI, Sonic Studio Virtual Mixer, BIOS

FlashBack button, BIOS FlashBack LED, M.2 heatsink		
Priključci na zadnjem panelu	DisplayPort priključci:	1x DisplayPort 1.4
	HDMI priključci:	1x HDMI 2.1
	Ukupno USB priključaka:	9
Reklamacioni period	Reklamacioni period:	36 meseci
Skladišni interfejs	SATA priključci (ukupno):	4
	SATA priključci:	SATA III 6Gbps
	Ostali skladišni interfejs:	3x M.2 Socket 3 (SSD)
Slotovi	PCI Express x16 slot:	1x PCI Express 3.0 (x4 mode), 1x PCI Express 5.0 (x16 mode)
	PCI Express x1 slot:	2x PCI Express 3.0
	PCI slot:	4