



Firma: ISCom d.o.o.  
Adresa: T.C. "Danubius" Karadorđeva 12,  
lokali 28, 156 i 156a  
Telefon: 026/4-100-500, 069/4-100-500  
Fax:  
PIB: 104927929  
E-mail: prodaja@iscom.rs

## NAS Synology RS422+ RackStation 4-bay

Šifra: 55376

Kategorija proizvoda: NAS uređaji

Proizvođač: SYNOLOGY



**Cena: 165.011,00 rsd.**

Hardware Specifications		
<b>CPU</b>	CPU Model	AMD Ryzen R1600
	CPU Quantity	1
	CPU Core	2
	CPU Architecture	64-bit
	CPU Frequency	2.6 (base) / 3.1 (turbo) GHz
	Hardware Encryption Engine	
<b>Memory</b>	System Memory	2 GB DDR4 ECC
	Notes	Synology reserves the right to replace memory modules with the same or higher frequency based on supplier's product life cycle status. Rest assured that the compatibility and stability have been strictly verified with the same benchmark to ensure identical performance.
<b>Storage</b>	Drive Bays	4
	Drive Type ( <a href="#">See all supported drives</a> )	3.5" SATA HDD      2.5" SATA SSD
	Hot Swappable Drive*	
<b>External Ports</b>	RJ-45 1GbE LAN Port	2
	USB 3.2 Gen 1 Port*	1
	Notes	This device's 1GbE LAN ports have a maximum transmission unit (MTU) size of 1,500 bytes.  The USB 3.0 standard was renamed to USB 3.2 Gen 1 by the USB Implementers Forum (USB-IF) in 2019.
<b>PCIe</b>	PCIe Expansion	1 x Gen3 x2 network upgrade slot
<b>Appearance</b>	Form Factor (RU)	1U
	Size (Height x Width x Depth)	44 mm x 478 mm x 327.5 mm
	Weight	4.38 kg

	Rack Installation Support*	4-post 19" rack (Synology Rail Kit - <a href="#">RKM114/RKS-02</a> )	2-post 19" rack (direct mounting)
	Notes	The rail kit is sold separately	
<b>Others</b>	System Fan	40 mm x 40 mm x 3 pcs	
	Fan Speed Mode	Full-Speed Mode Quiet Mode	Cool Mode
	Power Recovery		
	Noise Level*	28.5 dB(A)	
	Scheduled Power On / Off		
	Wake on LAN / WAN		
	Power Supply Unit / Adapter	100 watts	
	AC Input Power Voltage	100V to 240V AC	
	Power Frequency	50/60 Hz, Single Phase	
	Power Consumption	37.93 watts (Access) 13.43 watts (HDD Hibernation)	
	British Thermal Unit	129.42 BTU/hr (Access) 45.83 BTU/hr (HDD Hibernation)	
	Notes	For more information on how power consumption is measured, refer to <a href="#">this article</a> .	Noise testing was conducted with the Synology system fully installed with Synology SATA HDDs and in an idle state. Two G.R.A.S. Type 40AE microphones are placed at a 1 m distance from the front and rear of the device. Background noise: 16.49-17.51 dB(A); Temperature: 24.25-25.75°C; Humidity: 58.2-61.8%
<b>Temperature</b>	Operating Temperature	0°C to 35°C (32°F to 95°F)	
	Storage Temperature	-20°C to 60°C (-5°F to 140°F)	
	Relative Humidity	5% to 95% RH	
<b>Certification</b>	FCC BSMI RCM EAC KC	CE VCCI UKCA CCC BIS	
<b>Warranty</b>	3-year hardware warranty, extendable to 5 years with <a href="#">EW201</a> or <a href="#">Extended Warranty Plus</a>		
	Notes	The warranty period starts from the purchase date as stated on your purchase receipt. ( <a href="#">Learn more</a> )	<a href="#">Extended Warranty Plus</a> is only available in Europe and North America. <a href="#">EW201/EW202</a> is only available in Asia, Africa, and Oceania. For exact availability information please visit their respective websites.
<b>Environment</b>	RoHS Compliant		
<b>Packaging Content</b>	Main Unit X 1 AC Power Cord X 1	Accessory Pack X 1 Quick Installation Guide X 1	

<b>Optional Accessories</b>	Enterprise Series 3.5" SATA HDD: <a href="#">HAT5300 Series</a>	Plus Series 3.5" SATA HDD: <a href="#">HAT3300 Series</a>
	Enterprise Series 2.5" SATA SSD: <a href="#">SAT5200 Series</a> Rail Kit Sliding: <a href="#">RKS-02</a>	10GbE Network Upgrade Module: <a href="#">E10G22-T1-Mini</a> Rail Kit Mounted: <a href="#">RKM114*</a>
	Notes	Certain items may not be available in your location. Please contact your local distributors for more information.

<b>DSM Specifications</b>			
<b><a href="#">Storage Management</a></b>	Maximum Single Volume Size	108 TB	
	Maximum Internal Volume Number	64	
	SSD Read/Write Cache ( <a href="#">Determining cache size</a> )		
	SSD TRIM		
	Supported RAID Type	Synology Hybrid RAID JBOD RAID 1 RAID 6	Basic RAID 0 RAID 5 RAID 10
	RAID Migration	Basic to RAID 1 RAID 1 to RAID 5	Basic to RAID 5 RAID 5 to RAID 6
	Volume Expansion with Larger HDDs	Synology Hybrid RAID RAID 5 RAID 10	RAID 1 RAID 6
	Volume Expansion by Adding a HDD	Synology Hybrid RAID RAID 5	JBOD
	Global Hot Spare Supported RAID Type	Synology Hybrid RAID RAID 5	RAID 1
	Notes	Usable capacity for each volume will be lower than the maximum volume size and is dependent on the filesystem and the amount of system metadata stored.	Actual maximum storage pool and volume sizes depend on drive sizes used, the number of drive bays available, and the RAID configuration.
<b><a href="#">File System</a></b>	Internal Drives	Btrfs	ext4
	External Drives	Btrfs ext3 NTFS exFAT	ext4 FAT HFS+
<b><a href="#">File Services</a></b>	File Protocol	SMB NFS WebDAV	AFP FTP Rsync
	Maximum Concurrent SMB/AFP/FTP Connections	500	
	Windows Access Control List (ACL) Integration		
	NFS Kerberos Authentication		
	Notes	The testing standard was based on the maximum number of concurrent connections supported by this model. During the testing, 25% of the	

		connections were used to transfer files concurrently. The transfer process guaranteed that the connections were not interrupted; the minimum transfer speed was not guaranteed.
<b><u>Account &amp; Shared Folder</u></b>	Maximum Local User Accounts	2,048
	Maximum Local Groups	256
	Maximum Shared Folder	512
	Maximum Shared Folder Sync Tasks	8
<b><u>Hybrid Share</u></b>	Maximum Hybrid Share Folders	10
<b><u>Hyper Backup</u></b>	Folder and Package Backup	
	Entire System Backup	
	Notes	Full-system backup requires DSM 7.2 or later.
<b><u>High Availability</u></b>	Synology High Availability	
<b><u>Log Center</u></b>	Syslog Events per Second	800
<b><u>General Specifications</u></b>	Supported Protocols	SMB1 (CIFS), SMB2, SMB3, NFSv3, NFSv4, NFSv4.1, NFS Kerberized sessions, iSCSI, HTTP, HTTPS, FTP, SNMP, LDAP, CalDAV
	Supported Browsers	Chrome Edge Firefox Safari
	Supported Language	English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svenska, Nederlands, ???????, Polski, Magyar, Português do Brasil, Português Europeu, Türkçe, Český, ???????, ???, ???, ?????, ????
	Notes	For an updated list of supported browser versions, check the <a href="#">DSM Technical Specifications</a> .
<b>Add-on Packages <a href="#">view the complete package list</a></b>		
<b><u>Central Management System</u></b>		
<b><u>Synology Chat</u></b>	Suggested Users	100
	Notes	Measured with simulated users, each with an average record of 20,000 messages, emojis, or stickers. The required server response time is below ten seconds. Models with expandable memory are tested with their maximum supported memory.
<b><u>Download Station</u></b>	Maximum Concurrent Download Tasks	80
<b><u>SAN Manager</u></b>	Maximum iSCSI Target Number	128
	Maximum LUN	256
	LUN Clone/Snapshot, Windows ODX	
<b><u>Media Server</u></b>	DLNA Compliance	
<b><u>Synology Photos</u></b>	Facial Recognition	
<b><u>Snapshot Replication</u></b>	Maximum Snapshots per Shared Folder	1,024
	Maximum of System Snapshots	65,536

<a href="#">Surveillance Station</a>	Default Licenses	2 ( <a href="#">Additional cameras require purchase of licenses</a> ).	
	Suggested Maximum IP Cameras and Total FPS (H.264)	1080p: 40 channels, 800 FPS 5M: 28 channels, 280 FPS	3M: 35 channels, 350 FPS 4K: 17 channels, 170 FPS
	Suggested Maximum IP Cameras and Total FPS (H.265)	1080p: 40 channels, 1200 FPS 5M: 40 channels, 480 FPS	3M: 40 channels, 600 FPS 4K: 20 channels, 200 FPS
	Notes	<p>Performance figures are obtained from testing conducted with the device fully populated with drives, with their default memory configuration, and under a continuous recording setup. Actual system capabilities may vary based on configuration, drive performance, enabled features, and the presence of additional workloads.</p> <p>The number of streams that can be viewed simultaneously is <b>twice</b> the suggested maximum number of cameras. For example, if the suggested maximum number of cameras for a model is 10 under H.264, 1080p, the model can support up to 20 streams of the same specification at the same time.</p>	Use <a href="#">NVR Selector</a> to quickly find a suitable model based on your requirements.
<a href="#">Synology Drive</a>	Recommended Number of Concurrent Sync Clients	350 (the number of connections that can be maintained when the recommended number of hosted files was reached)	
	Recommended Number of Hosted Files	5,000,000 (applies to files indexed or hosted by <a href="#">Synology Drive</a> . For file access through other standard protocols, refer to the File Services section above)	
	Notes	<p>Exceeding the recommended numbers above will not block application operations, but may result in longer response time.</p> <p>Btrfs file system and non-encrypted shared folders were used during the aforementioned testing.</p>	Utilizing SSD cache can significantly improve performance.
<a href="#">Synology Office</a>	Suggested Users	3,000	

	Notes	Suggested users is derived from testing in an environment with 60% idle users (each logging in and viewing documents) and 40% active users (each executing random actions at intervals of 20 to 40 seconds) operating within documents, each document having 30 users. <a href="#">Learn more</a>	Client performance may affect maximum simultaneous editing users. Client PCs used for testing: Intel Core i3-3220 / 8GB RAM
--	-------	---	---

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.