



Firma: ISCom d.o.o.  
Adresa: T.C. "Danubius" Karađorđeva 12,  
lokali 28, 156 i 156a  
Telefon: 026/4-100-500, 069/4-100-500  
Fax:  
PIB: 104927929  
E-mail: prodaja@iscom.rs

## USW-PRO-MAX-24-POE-EU ( USW-PRO-MAX-24- POE-EU )

Šifra: 56555

Kategorija proizvoda: Switch uređaji

Proizvođač: UBIQUITI



**Cena: 135.952,00** rsd.

|                                 |   |
|---------------------------------|---|
| Warranty Term (month):          | 12 month(s)   |
| Pack Weight Brutto (kg):        | 6.053 kg  |
| Pack Weight Netto (kg):         | 3.7 kg  |
| Pieces in pack:                 | 1   |
| Box Weight Brutto (kg):         | 13.64 kg  |
| Number of Ports:                | 8 x (2.5 Gbps) RJ-45 16 x 10Base-T 100Base-TX 1000Base-T (Gigabit Ethernet Fast Ethernet Ethernet) RJ-45 2 x (10 Gbps) SFP+ |
| Total Number of Ports:          | 26  |
| Switching Layers:               | Layer 2<br>Layer 3  |
| Data Bit Rate:                  | 112 Gbps  |
| Network Transport Protocol:     | DHCP<br>IGMP<br>STP<br>RSTP<br>LLDP   |
| Networking Compliant Standards: | IEEE 802.1X   |
| Networking Features:            | Jumbo Frames Support<br>8 Ports PoE+<br>8 Ports PoE++   |
| Device Location:                | External  |
| Mounting Capability:            | Rackmount   |
| Standard Rack Height:           | 1U  |
| Certifications:                 | CE, FCC, IC   |
| LAN:                            | 24 (RJ-45)  |
| SFP+:                           | 2   |
| Power Supply:                   | Internal<br>AC 100-240 V  |
| Power over Ethernet:            | External  |
| Maximum Output Power:           | 450 W   |
| Depth (mm):                     | 325 mm  |
| Height (mm):                    | 44 mm   |
| Width (mm):                     | 442 mm  |
| Nominal Weight:                 | 5.1 kg  |
| External Color:                 | Gray  |
| Maximum Operating Ambient       |   |

|  |       |
|--|-------|
| Temperature:                           | 40 °C |
| Maximum Operating Humidity:            | 90 %  |
| Minimum Operating Ambient Temperature: | -5 °C |
| Minimum Operating Humidity:            | 10 %  |