



Firma: ISCom d.o.o.
Adresa: T.C. "Danubius" Karađordeva 12,
lokali 28, 156 i 156a
Telefon: 026/4-100-500, 069/4-100-500
Fax:
PIB: 104927929
E-mail: prodaja@iscom.rs

ASUS ROG CROSSHAIR X870E APEX matična ploča(PLO03764)

Šifra: 57402

Kategorija proizvoda: AMD matične ploče

Proizvođač: ASUS

Cena: **100.743,00** rsd.



Audio	Broj kanala: Model: Napomena:	7.1 Realtek ALC4080 Codec Jack-detection, Multi-streaming, Front Panel Jack-retasking, Premium audio capacitors, Audio Cover, Supports up to 32-Bit 384 kHz playback, SupremeFX Shielding, Savitech SV3H712 AMP, Podrška za S PDIF output, Gold-plated jacks, High quality 120dB SNR stereo playback output and 110dB SNR recording input, Impedance sense for front and rear headphone outputs
Fizičke karakteristike	Format: Dimenzije: Pakovanje:	ATX 305mm x 244mm 1 x ASUS Wi-Fi antena, 4 x SATA 6Gb s kabl, 1 x ASUS WiFi Q-Antenna, 1 x ROG DIMM.2 with heatsink, 1 x M.2 pad for ROG DIMM.2, 2 x M.2 screw package for ROG DIMM.2, 1 x ROG Memory Fan Kit, 1 x Q-connector, 3 x M.2 Q-Slide package, 3 x M.2 rubber package, 1 x ROG stickers, 1 x ROG Bottle Opener, 1 x USB drive with utilities and drivers
Memorija	Tip memorije: Memorijski slotovi: Podržane memorije:	DDR5 2x DDR5 Podrška DDR5 memorije do 9.600+MT s (O.C.)
Mreža	Žična mreža (LAN): Model: Wi-Fi:	1x Realtek 5Gb Ethernet Realtek Da
Osnovne karakteristike	Procesorsko ležište (socket): Čipset:	AMD AM5 AMD X870E
Ostale karakteristike	Podržane tehnologije:	AURA Creator, AURA Sync, DIGI+VRM, SafeSlot, Q-DIMM, VRM heatsink design, M.2 Q-Latch, SafeDIMM, ASUS UEFI BIOS EZ Mode, ASUS CrashFree

BIOS 3, Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green]), Q-Antenna, M.2 heatsink, UEFI Bios, ProCool II, Fan Xpert 4, GameFirst, Q-Connector, MyHotkey, Q-Dashboard, Extreme Engine Digi+, ROG CPU-Z, AI Cooling II, CPU Socket lever protector, AI Overclocking, AI Advisor, PCIe Slot Q-Release Slim, M.2 Q-Release, Q-Code, M.2 Q-Slide, FlexKey, Metal backplate, Dolby Atmos, USB Wattage Watcher, TurboV Core, Extreme OC Kit, M.2 heatsink backplate, Pre-mounted I/O shield, ASUS EZ Flash, AIDA64 Extreme (1 year full version), HWiNFO, DriverHub, GlideX

Priključci na zadnjem panelu	DisplayPort priključci:	Da preko USB-C
	PS 2:	1 (tastatura ili miš)
	Ukupno USB priključaka:	10
Reklamacioni period	Reklamacioni period:	36 meseci
Skladišni interfejs	SATA priključci (ukupno):	4
	SATA priključci:	SATA III 6Gbps
	Broj M.2 slotova:	5
Slotovi	PCI Express x16 slot:	2x PCI Express 5.0 (x16 ili x8 x8 ili x8 x4 x4 modovi)
	PCI Express x4 slot:	1x PCI Express 4.0
	PCI Express x1 slot:	1x PCI Express 3.0