



Firma: ISCom d.o.o.
Adresa: T.C. "Danubius" Karađorđeva 12,
lokali 28, 156 i 156a
Telefon: 026/4-100-500, 069/4-100-500
Fax:
PIB: 104927929
E-mail: prodaja@iscom.rs

DAHUA IPC-HDBW3549R1-ZAS-PV 5MP Smart
Dual Light Active Deterrence Vari-focal Dome
WizSense Network Camera (SCA01092)

Šifra: 58754
Kategorija proizvoda: IP kamere za video nadzor
Proizvođač: Dahua



Cena: **85.125,00** rsd.

Audio	Zvučnici: Mikrofon: Podržani audio formati:	Ugrađeni Ugrađen G.726, PCM, G.711a, G.711Mu, G.723
Dodatne funkcije	Snimanje:	Video tampering, Scene changing, Detekcija zvuka, BLC, HLC, Detekcija pokreta, WDR, Detekcija ljudskog oblika, Detekcija vozila, voltage detection, privacy masking, Manual gain control, SSA, Smart Illumination, 3D DNR, Image Rotation, Mirror, EIS, Defog, AWB, AGC, IP address conflict, Network disconnection, Ručni balans bele, BRC, IVS, SMD, Alarm Event, AI SSA, AcuPick, Dan noć Auto(Electronic) Color B W
Fizičke karakteristike	Dimenzije: Masa: Boja:	Φ126mm x 105mm 730g Bela
Memorija	Podržane memorijske kartice:	MicroSD (do 512GB), FTP, SFTP
Reklamacioni period	Reklamacioni period:	24 meseca
Senzor	Tip kamere: Rezolucija senzora: Veličina:	IP 5 Megapiksela 1 2.7 inča
Snimanje videa	Rezolucija videa: Frame rate: Podržani video formati:	1.920 x 1.080 (Full HD 1080p), 1.280 x 720, 1.280 x 960 (1.3M), 704 x 576 (D1), 704 x 480 (D1), 640 x 480 (VGA), 352 x 288 (CIF), 352 x 240 (CIF), 2.592 x 1.944 (5M), 2.304 x 1.296 (3M), 2.688 x 1.520 (4M), 2.880 x 1.620 (5M) 1~25 30fps H.264, H.264B, H.264H, H.265, MJPEG, Smart H.264+, Smart

H.265+

Sočivo	Fokusna daljina:	2.7mm~13.5mm
	Fokusni koeficijent:	F1.0
Zaštita	Ostalo:	802.1x, Digest, WSSE, account lockout, security logs, Generation and importing of X.509 certification, HTTPS, trusted boot, trusted execution, trusted upgrade, IP MAC filtering, Syslog
Žična mreža	Protok žične mreže: Protokoli:	RJ-45 (10 100Mbps Base-T) IPv4, ARP, TCP, UDP, ICMP, RTSP, RTP, RTCP, IPv6, HTTP, FTP, NTP, SMTP, DNS, DDNS, PPPOE, DHCP, IGMP, SNMP, QoS, Multicast, NFS, SFTP, RTMP, UPnp, P2P