



Firma: ISCom d.o.o.
Adresa: T.C. "Danubius" Karađorđeva 12,
lokali 28, 156 i 156a
Telefon: 026/4-100-500, 069/4-100-500
Fax:
PIB: 104927929
E-mail: prodaja@iscom.rs

POS-BS1100R GMB 2d CMOS barcode scanner, 2000mAh, BT/WiFi

Šifra: 66591

Kategorija proizvoda: Barkod čitači

Proizvođač: GEMBIRD

Cena: 5.831,00 rsd.

OS Windows / iOS / Android	Image Sensor CMOS	Image(Pixels) 640 (H) x 480 (V) pixels	Light source Illuminating 625 nm LED Illumination 40000 LUX	Scan Mode Handheld (Manual) / Handheld (Automatic) / Handheld (Automatic) / Handheld (Automatic)
FPS 300fps	Scan accuracy ± 4mm @ Code 39	Print Contrast ≥ 30%	Visual Indicator Green LED light, Buzzer, motor vibration	Transmission Range 2.4G/100m; Bluetooth H4/DB/E/ SPP 40m (in open air)
Scan Angle Left and right: ± 55° Front and top: ± 55° Rotate: 360°	Field of view 32° horizontal, 24° vertical	Work frequency 2.400GHz-2.480GHz ISM frequency	Dimension H x W x L 179x84x44 (mm)	Weight 170g (With USB Dongle)
Case Material ABS+PC, TPU	Memory Capacity 380000 byte	Power parameter Input Voltage: 5VDC/5V, Working current: 400mA	Firmware Update Computer online upgrade	Scan distance 20-300mm @ EAN 13 and PCS-100%, 5-170mm @ QR 2D and PCS-100%
Paired Mode one to one, or one to more (Optional)	Battery Parameters Battery Capacity: 2000mAh Charge Mode: Wire charging Charge time: 1h Working time: 12h (continuous scanning)	Safety regulations CE (EN 60950-1:2005), EN 15005:2017, RoHS, EN62368-1:2014+11:2017 FCC PART 15 CLASS B	Environmental parameters Operating Temperature: 0°C ~ 40°C Storage Temperature: -20°C ~ 60°C Relative humidity: 10% ~ 90% (non-condensing) Maximum pressure: 1013 hPa (760 mmHg) Maximum height: 1000m (3280ft) Drop resistance: 1.8m (6ft) IPX2	

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.